



## TECHNICAL DATA SHEET

### DESCARGA DE GASOLINA

CODIGO	DIAMETRO INTERNO		DIAMETRO EXTERNO	PRESIÓN MÁXIMA DE TRABAJO		PRESIÓN MÍNIMA DE RUPTURA		ROLLO		PESO	
CODE	INTERNAL DIAMETER		EXTERNAL DIAMETER	MAXIMUM WORKING PRESSURE		BURST PRESSURE		ROLL		WEIGHT	
	IN	MM	MM	PSI	BAR	PSI	BAR	MTS	PIE	KG/MTS	LB/PIE
DGI-150	1-1/2"	38,10	50	150	10,34	450	31,03	30	98,42	0,89	0,62
DGI-200	2"	50,80	61	150	10,34	450	31,03	30	98,42	1,25	0,87
DGI-250	2-1/2"	63,50	76	150	10,34	450	31,03	30	98,42	1,35	0,93
DGI-300	3"	76,20	90	150	10,34	450	31,03	30	98,42	1,67	1,16
DGI-400	4"	101,60	116	150	10,34	450	31,03	30	98,42	1,86	1,29
DGI-600	6"	152,40	168	150	10,34	450	31,03	20	65,62	5,13	3,55
DGI-800	8"	203,20	220	150	10,34	450	31,03	20	65,62	6,40	4,43

#### Aplicación:

Descarga de gasolina, para la construcción, agricultura e industrias

#### Ventajas:

Resistente a la gasolina y derivados del petróleo, de fácil manejo

#### Tubo:

Mezcla de goma sintética, NBR

#### Refuerzo:

Capas textiles, altamente resistentes

#### Cubierta:

Mezcla de goma sintética, NBR

#### Color de Cubierta:

Negro con franja naranja

#### Marcado:

PROFIX ( DGI ) GASOLINE DISCHARGE (XX"- XX MM I.D.)  
MAX. W.P. XXX PSI / XX BAR

#### Rango de Temperatura:

Desde -32°C to + 92°C.

#### Aplicación

Discharge of gasoline, for construction, agriculture and industries

#### Advantage

Resistant to gasoline and petroleum products, easy to handle

#### Tube

Synthetic rubber mix, NBR

#### Reinforcement

Textile layers, highly resistant

#### Cover

Synthetic rubber mix, NBR

#### Cover Color

Black, with an orange stripe

#### Branding

PROFIX ( DGI ) GASOLINE DISCHARGE (XX"- XX MM I.D.)  
MAX. W.P. XXX PSI / XX BAR

#### Temperature range

-32°C to + 92°C.