



TECHNICAL DATA SHEET

JARDÍN TRABAJO MEDIANO CON CONEXIONES M X H

CODIGO	DIAMETRO INTERNO		DIAMETRO EXTERNO	PRESIÓN MÁXIMA DE TRABAJO		PRESIÓN MÍNIMA DE RUPTURA		ROLLO		PESO	
CODE	INTERNAL DIAMETER		EXTERNAL DIAMETER	MAXIMUM WORKING PRESSURE		BURST PRESSURE		ROLL		WEIGHT	
	IN	MM	MM	PSI	BAR	PSI	BAR	MTS	PIE	KG/MTS	LB/PIE
PVIG-050-25	1/2"	13	20	300	20,69	900	62,06	7,62	25,00	0,20	0,14
PVIG-050-50	1/2"	13	20	300	20,69	900	62,06	15,24	50,00	0,20	0,14
PVIG-050-100	1/2"	13	20	300	20,69	900	62,06	30,48	100,00	0,20	0,14
PVIG-062-25	5/8"	16	25	300	20,69	900	62,06	7,62	25,00	0,34	0,24
PVIG-062-50	5/8"	16	25	300	20,69	900	62,06	15,24	50,00	0,34	0,24
PVIG-062-100	5/8"	16	25	300	20,69	900	62,06	30,48	100,00	0,34	0,24
PVIG-075-25	3/4"	19	28	300	20,69	900	62,06	7,62	25,00	0,39	0,27
PVIG-075-50	3/4"	19	28	300	20,69	900	62,06	15,24	50,00	0,39	0,27
PVIG-075-100	3/4"	19	28	300	20,69	900	62,06	30,48	100,00	0,39	0,27

Aplicación:

Descarga de agua, para el hogar, residencias, la agricultura e industrias en general

Ventajas:

Resistente a la intemperie, liviana y de fácil manejo. Incluye conexiones de bronce macho y hembra para su rápido uso

Tubo:

PVC

Refuerzo:

Trenzado textil, altamente resistente

Cubierta:

PVC

Color de Cubierta:

Azul

Marcado:

PROFIX (PVIG) GARDEN MEDIUM DUTY - WATER (XX"- XX MM I.D.) MAX. W.P. 300 PSI / 20 BAR

Rango de Temperatura:

Desde -35°C to + 60°C.

Aplicación

Discharge of water, for the home, residences, agriculture and industries in general

Advantage

Weather-resistant, lightweight and easy to handle. Includes male and female bronze connections for quick use

Tube

PVC

Reinforcement

Textile braid, highly resistant

Cover

PVC

Cover Color

Blue

Branding

PROFIX (PVIG) GARDEN MEDIUM DUTY - WATER (XX"- XX MM I.D.) MAX. W.P. 300 PSI / 20 BAR

Temperature range

-35°C to 60°C.