



TECHNICAL DATA SHEET

JARDIN TRABAJO PESADO CON CONEXIONES M X H

CODIGO	DIAMETRO INTERNO		DIAMETRO EXTERNO	PRESIÓN MAXIMA DE TRABAJO		PRESIÓN MINIMA DE RUPTURA		ROLLO		PESO	
CODE	INTERNAL DIAMETER		EXTERNAL DIAMETER	MAXIMUM WORKING PRESSURE		BURST PRESSURE		ROLL		WEIGHT	
	IN	MM	MM	PSI	BAR	PSI	BAR	MTS	PIE	KG/MTS	LB/PIE
TPIG-050-25	1/2"	13	20	300	20,69	900	62,06	7,62	25,00	0,25	0,17
TPIG-050-50	1/2"	13	20	300	20,69	900	62,06	15,24	50,00	0,25	0,17
TPIG-050-100	1/2"	13	20	300	20,69	900	62,06	30,48	100,00	0,25	0,17
TPIG-075-25	3/4"	19	28	300	20,69	900	62,06	7,62	25,00	0,45	0,31
TPIG-075-50	3/4"	19	28	300	20,69	900	62,06	15,24	50,00	0,45	0,31
TPIG-075-100	3/4"	19	28	300	20,69	900	62,06	30,48	100,00	0,45	0,31

Aplicación:

Descarga de agua, para el hogar, residencias, minería, la agricultura e industrias en general

Ventajas:

Resistente a la intemperie, liviana y de fácil manejo. Incluye conexiones de bronce macho y hembra para su rápido uso

Tubo:

Mezcla de goma termoplástica (TPR)

Refuerzo:

Trenzado textil, altamente resistente

Cubierta:

Mezcla de goma termoplástica (TPR)

Color de Cubierta:

Rojo

Marcado:

PROFIX (TPIG) HEAVY DUTY - WATER (XX"- XX MM I.D.)
MAX. W.P. 300 PSI / 20 BAR

Rango de Temperatura:

Desde -40°C to + 70°C.

Aplicación

Water discharge, for the home, residences, mining, agriculture and industries in general

Advantage

Weather-resistant, lightweight and easy to handle. Includes male and female bronze connections for quick use

Tube

Thermoplastic rubber mix (TPR)

Reinforcement

Textile braid, highly resistant

Cover

Thermoplastic rubber mix (TPR)

Cover Color

Red

Branding

PROFIX (TPIG) HEAVY DUTY - WATER (XX"- XX MM I.D.)
MAX. W.P. 300 PSI / 20 BAR

Temperature range

-40°C to 70°C.