



TECHNICAL DATA SHEET

NO TÓXICA CON REFUERZO DE ACERO

CODIGO	DIAMETRO INTERNO		DIAMETRO EXTERNO	PRESIÓN MÁXIMA DE TRABAJO		PRESIÓN MÍNIMA DE RUPTURA		ROLLO		PESO	
CODE	INTERNAL DIAMETER		EXTERNAL DIAMETER	MAXIMUM WORKING PRESSURE		BURST PRESSURE		ROLL		WEIGHT	
	IN	MM	MM	PSI	BAR	PSI	BAR	MTS	PIE	KG/MTS	LB/PIE
PSI-025	1/4"	6	11	75	5,17	225	15,51	100	328,08	0,25	0,17
PSI-031	5/16"	8	14	75	5,17	225	15,51	100	328,08	0,30	0,21
PSI-038	3/8"	9	15	75	5,17	225	15,51	100	328,08	0,35	0,24
PSI-050	1/2"	12	18	75	5,17	225	15,51	100	328,08	0,45	0,31
PSI-062	5/8"	15	22	75	5,17	225	15,51	100	328,08	0,63	0,44
PSI-075	3/4"	19	25	75	5,17	225	15,51	50	164,04	0,61	0,42
PSI-100	1"	25	33	75	5,17	225	15,51	50	164,04	1,10	0,76
PSI-125	1 1/4"	32	41	60	4,14	180	12,41	40	131,23	1,60	1,10
PSI-150	1 1/2"	38	47	60	4,14	180	12,41	40	131,23	2,05	1,42
PSI-200	2"	50	60	60	4,14	180	12,41	40	131,23	2,86	1,98
PSI-300	3"	75	88	45	3,10	135	9,31	30	98,42	5,73	3,97

Aplicación:

Succión de agua, alimentos, líquidos y materiales granulados. Para el sector industrial en general

Ventajas:

Liviana y de fácil manejo. Grado alimenticio

Tubo:

PVC

Refuerzo:

Alambre de acero en espiral

Cubierta:

PVC

Color de Cubierta:

Transparente

Marcado:

PROFIX (ASI) NON TOXIC - STEEL HELIX (XX"- XX MM I.D.) MAX. W.P. XXX PSI / XX BAR

Rango de Temperatura:

Desde -35°C to + 60°C.

Aplicación

Suction of water, food, liquids and granulated materials. For the industrial sector in general

Advantage

Light and easy to use. Alimentary grade

Tube

PVC

Reinforcement

Steel wire in spiral

Cover

PVC

Cover Color

Transparent

Branding

PROFIX (ASI) NON TOXIC - STEEL HELIX (XX"- XX MM I.D.) MAX. W.P. XXX PSI / XX BAR

Temperature range

-35°C to 60°C.